




Choose the Aquabot Model That's Right for You

	Aquabot Pool Rover Junior	Aquabot Pool Rover Hybrid	Aquabot Turbo T-Jet
			
	Self-contained mobile filtration system automatically vacuums, microfilters, and circulates flat-bottomed above-ground pool floors without using the pool's filter or extraneous hoses and connections. Cleans most pools in as little as 30 minutes without getting stuck.	Equipped with the primary features of the Junior, but can clean floors of any above-ground or in-ground pool.	Self-contained mobile filtration system hydroscrubs, vacuums, and microfilters in-ground pools from floor to waterline (rolling up radiuses) without using booster pumps or the pool's filter. Hoseless, automatic operation provides fast and efficient cleaning. Ideal for hard-surfaced pools in Sunbelt markets that require long-term reliability and low maintenance.
Pool Type	Above ground	Aboveground or in ground	In ground
Pool Surface/Shape	Flat-bottomed vinyl of any shape	All surfaces (up to 60° maximum incline) and shapes	All surfaces and shapes. Ideal for hard surfaces (pebbled, plaster, fiberglass). Minimum 6" radius (transition point from floor to wall) required to climb to waterline.
Maximum Pool Length	40'	40'	50'
Cable Length	41'	41'	51'
Cleaning (sq. ft. per hr.)	5,400	5,400	6,800
Cleaning Time (Most Pools)	30 mins.	1 hr.	1 hr.
Auto Shutoff Time	2 hrs.	2 hrs.	2 hrs. + Override capability for external timed operation
Adjustable Forward/Reverse Continuous Cleaning Timer	1 - 60 secs.	1 - 60 secs.	1 - 9 secs.
Wheels	Extra-wide, non-marring. Rolls over ripples, seams and footprint impressions.	Extra-wide, non-marring. Rolls over ripples, seams, footprint impressions, pop-up heads, and raised main drains.	Dense non-marring rubber; rolls over virtually anything.
Raised Surface Obstacle Avoidance	Large wheels, high body, and powerful pump to roll over obstacles with ease.	Large wheels, high body, and powerful pump to roll over obstacles with ease.	NeverStuck™ Rollers to roll over obstacles, such as raised floor drains, return fittings, in-floor pop-up heads, and convex lights.
Pump Motor	DC brushless; oil cooled/lubricated; externally water cooled	DC brushless; oil cooled/lubricated; externally water cooled	DC brushless; oil cooled/lubricated; externally water cooled
Debris Intake Ports	2 offset; for clog-free operation and corner access	2 offset; for clog-free operation and corner access	2 offset; clog-free; customizable: 1" x 5" each to 1.5" x 5" each
Suction Port Depths	Standard	Standard	3 customizable depths
Port Velocity Adjustments	N/A	N/A	Yes; for customized removal of fine dirt or large debris
Filtration Rate	4,200 gph	4,200 gph	4,800 gph
Filter Max Debris Holding Capacity	23 quarts	34 quarts	34 quarts; fine microfiltration and mesh macrofiltration filters included_
Embedded Dirt Removal Mechanism	N/A	N/A	DeepClean™ power wash/hydroscrubbing
Drive Feature	Single onboard pump; hydraulic jet drive propulsion system	Single onboard pump; hydraulic jet drive propulsion system	Single onboard pump; hydraulic jet drive propulsion system
Guidance	Directional Guidance Pin	Directional Guidance Pin	Directional Guidance Axle
Cleaner Weight	10.5 lbs.	10.6 lbs.	10.75 lbs.
Power Supply	Painted stainless weather-resistant	Painted stainless weather-resistant	StayCool™ all-weather resistant
Operating voltage	24	24	30
Wattage	140	140	150
Electricity Requirements	115 V/60 Hz	115 V/60 Hz	115 V/60 Hz
Warranty	1-year	2-year	3-year/200-cycle prorated