

## Trouble Shooting Steps

- Check to make sure old aerator washer was removed and only the new adapter washer is being used. • If the enclosed adapters do not fit, contact PUR Consumer Relations at 1-800-PUR-LINE (1-800-787-5463).

Adapters don't fit / won't stay attached / keep falling off.

Water leaks out around the filter cover. Slow water flow in the filtered position. Water leaks around the faucet adapter and faucet.

- Remove the filter cartridge and reinstall the filter cartridge again. • Replace the filter cartridge.

Difficulty in removing the old filter cartridge to replace the filter.

- Check to see that the washer was placed on top of the faucet adapter when installed. • Make sure the adapter is hand-tightened securely to the faucet. • Make sure the unit is securely attached to the faucet adapter. • Remove the filter system unit from the faucet by squeezing the quick release buttons. • Remove the cover. • Slowly turn or twist the filter cartridge. This will help loosen the filter.

### Technical Specifications:

FILTER CAPACITY: 100 gallons (378 liters)/ up to 3 months

RATED SERVICE FLOW: 0.52 gallons/minute (2.0 liters/minute) at 60 psig

MAXIMUM TEMPERATURE: 100°F (38°C)

MINIMUM TEMPERATURE: 34°F (1°C)

MAXIMUM WORKING PRESSURE: 100 psig (690 kPa)

MINIMUM WORKING PRESSURE: 20 psig (138 kPa)

For system to perform as shown in the Performance Data Sheet, it is necessary to replace the filter when it exceeds filter capacity (100 gallons). Testing was performed under standard laboratory conditions, actual performance may vary. The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water. Do not use with water that is microbiologically unsafe, or of unknown quality, without adequate disinfection before or after the system. Systems that are certified for cyst reduction may be used on disinfected water that may contain filterable cysts. Individuals requiring water of certain microbiological purity should consult their physician. Replacement filters may be purchased at most retail outlets or at [purwater.com](http://purwater.com).