

KOHLER® Roughing-In

K-3609
CIMARRON®
COMFORT HEIGHT® TOILET

Product Information

Applicable product:	
Left-hand trip lever (shown)	K-3609
Right-hand trip lever	K-3609-RA
Tank cover locks, left-hand trip lever	K-3609-T
Tank cover locks, right-hand trip lever	K-3609-TR
Insuliner® tank, left-hand trip lever	K-3609-U
Insuliner tank, right-hand trip lever	K-3609-UR

Fixture:	
Configuration	two-piece, elongated
Water per flush	1.28 gpf (4.8 lpf)
Passageway	2-1/8" (54 mm)
Water area	10-1/2" (267 mm) x 7-7/8" (200 mm)
Water depth from rim	6-3/8" (162 mm)
Seat post hole centers	5-1/2" (140 mm)

Included components:	
Bowl	K-4309
Tank cover	1086929 (cont.)

(cont.) Tank cover with locks	1086929-T
Trip lever, left-hand	1059436
Trip lever, right-hand	1116014
Bolt cap accessory pack	1013092
Tank accessory pack	1016548
Tank, left-hand trip lever, 1.28 gpf (4.8 lpf)	K-4421
Insuliner tank, left-hand trip lever, 1.28 gpf (4.8 lpf)	K-4421-U

Installation Notes

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

Will comply with the Americans with Disabilities Act (**ADA**) when installed per the requirements of the 2010 ADA Standards of Accessible Design, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** Barrier Free requirements when installed per Clause 3.8.3.8 and 3.8.3.9.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

