

	Model	Reolink Keen
Hardware Features	Image Sensor	1/2.7" CMOS Sensor
	Display Resolution	1920x1080 (2.0 Megapixels)
	Lens	f=4.0 mm Fixed, F=2.0, with IR Cut
	Angle of View	Horizontal: 90°
		Vertical: 45°
	Pan/Tilt Angle	Horizontal: 355°
		Vertical: 105°
	Minimum Illumination	0 Lux (With IR Illuminator)
	IR Distance	12 Meters (40ft)
	Dimension	103×95×117 mm
	Weight (Battery Included)	380 g
	Interface	Built-in Micro SD Card Slot
Built-in Microphone and Speaker		
Reset Button		
Software Features	Protocols & Standards	SSL, TCP/IP, UDP, SMTP, DHCP, DNS, P2P
	Image Compression	H.264
	Maximal Frame Rate	15fps
	Code Rate	768Kbps~2048Kbps
	Audio	Two-Way Audio
	Maximal User Access	Support up to 8 simultaneous video streams
	Browser Supported	Not Available
	Access to Camera	Smart Phone: iOS, Android Computer: Windows, Mac
	Standby Awaken	PIR Alarm, Remote Access, Reset Button
	Record Mode	PIR Alarm Record
WiFi	Wireless Standard	IEEE 802.11b/g/n
	Operating Frequency	2.4 GHz
	Wireless Security	WEP/WPA-PSK/WPA2-PSK
Battery	Type Specification	Four (4) Lithium CR123A/3.0V Photo
	Battery Level Indication	Yes
	Ordinary Life	4-6 Months
	Endurance Ability	Daytime: 10 Hours; Night Vision: 5 Hours
Other Parameters	Temperature	Operating Temperature: -10°C~+55°C
		Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20%~85%
		Storage Humidity: 10%~90%
Waterproof	No	

Hardware Features	Model	PIR Sensor
	Detecting Distance	8M (26ft)
	Detecting Angle	Horizontal: 120°, Vertical: 60°
	Transmitting Frequency	433MHz (Wireless)
	Transmitting Distance	200M (Accessibility)
	Battery Type	One (1) Lithium CR123A/3.0V Photo
	Battery Life	3 Years
	Dimension	100x66.5x36.5 mm
	Weight (Battery Included)	65 g
	Temperature	Operating Temperature: -10°C~+55°C
		Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20%~85%
		Storage Humidity: 10%~90%
	Waterproof	No