

Smart Card Reader ST-1044 Smart Terminal



USB SC Reader

ST-1044 popular smart card reader with a weighted base provides a stable one hand operation for Smart Card insertion and extraction. Whether used for access, monitoring network logon or chipcard-based Internet transactions - the Smartcard Reader with USB connection is the perfect solution.

Key Features

- High-quality USB smart card reader
- CardMan 3121 compatible
- USB 2.0 compatible
- "Single-handed operation" weighted base increases stability
- PC/SC smart card reader
- CT-API and OCF support
- Protocols: T=0, T=1, S=8, S=9, S=10
- CCID compatible
- FIPS 201 Certified
- TAA Compliant

Technical Data:

Housing color:

- Light grey with a black base

Weight (product):

- Approx 300 g
- 0.66 lbs

Total weight (with packaging):

- 350 g
- .77 lbs

Cable Length:

- Approx. 1.75 m
- Approx. 5.74 ft.

Storage Temperature:

- -20°C to 60°C
- -4°F to 140°F

Operating Temperature:

- -0°C to 50°C
- 32°F to 122°F

Smart Card Speed:

- Up to 412,903 bps legend

Current Consumption:

- Max. 100 mA

Interface:

- USB

System Requirements:

- USB connection

Product Approvals:

- cURus
- VDE GS
- VCCI
- CE
- FCC
- VDE
- FIPS 201



Delivery Volume:

- SmartTerminal ST-1044U
- CD-ROM software
- Operating instructions in hard copy

Insertion Cycles:

- Approx. 100,000 hours

Operating systems:

- Windows98, CE 5.0 (CE.NET), ME, 2000, XP, XP 64 Bit IA64 and AMD64, Linux PC/SC, Mac OS

Dimensions (product):

- 75 x 51 x 55 mm
- 2.95" x 2.01" x 2.17" inches

Dimensions (packaging):

- 128 x 195 x 60 mm
- 5.02" x 7.68" x 2.36"

Packing Unit:

- Number of products in the master package: 64
- Number of master packages per pallet: 6

Warranty

- 2 years

Technical Data Continued:

Smartcard-Reader:

- Hardware interface: USB
- Agency Approvals: EMV 2000 Level 1
- Chip-card protocols: T=0, T=1, S=8, S=9, S=10
- Contact: mechanical swipe reader
- Software interface: CT-API, PC/SC, CCID
- Mating cycles: approx. 100,000 operations
- Compatible chip card types: Reads and writes on all 5V, 3V and 1.8V Smart Cards 7816 Class A, B and C cards
- Transmission speed reader ↔ card: 412,903 Bit/s
- Transmission speed reader ↔ system: max 12 MBit/s
- Chip card pulse frequency: 4.8 MHz

Errors, technical changes and delivery possibilities excepted.
Technical information refers only to the specifications of the products. Features may differ from the information provided.

Model: ST-1044 Smart Card Reader

<i>Product name</i>	<i>Order Number</i>	<i>Packaging</i>
Smart Card Reader SmartTerminal ST1044	ST-1044UB	White box

ZF Electronics Corporation
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6500
Internet: www.cherrycorp.com

Sales: 262.942.6562
E-Mail: CEP_sales@zf.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.