



AT-LP60

FULLY AUTOMATIC STEREO TURNTABLE SYSTEM

2 SPEEDS – 33 1/3 AND 45 RPM



- Fully automatic operation
- Two speeds: 33 1/3 RPM and 45 RPM
- Professional aluminum turntable platter
- Integral Audio-Technica Dual Magnet™ phono cartridge with replaceable diamond stylus
- Built-in switchable stereo phono/line level pre-amplifier permits use of turntable with stereo systems having either magnetic-phono inputs or "AUX" (line-level) inputs; also allows convenient use of turntable with most powered speakers
- Damped lift/cueing mechanism with front-panel control
- Removable dust cover

Specifications*

Type: Belt drive turntable, fully automatic; **Platter:** Aluminum; **Motor:** DC servo-controlled; **Speeds:** 33 1/3 RPM, 45 RPM; **Wow and flutter:** Less than 0.25% (WTD) @ 3 kHz (JIS); **Signal-to-noise ratio:** >50 dB (DIN-B); **Cartridge:** Integral Dual Magnet™ stereo cartridge with diamond stylus; **Output level:** 2.5 mV nominal at 1 kHz, 5 cm/sec (Pre-amp "PHONO"); 150 mV nominal at 1 kHz, 5 cm/sec (Pre-amp "LINE"); **Phono pre-amp gain:** 36 dB nominal, RIAA equalized; **Power:** 120V AC, 60 Hz, 3W; **Dimensions:** 360.0 mm (14.17") W x 97.0 mm (3.84") H x 356.0 mm (14.02") D; **Net weight:** 2.98 kg (6.6 lbs.); **Furnished accessories:** Dual RCA (female) to 3.5 mm (1/8") mini-plug (male) stereo adapter cable; dual RCA (female) to 3.5 mm (1/8") mini-plug (female) stereo adapter cable; 45 RPM adapter; **Replacement stylus:** ATN3600L

*Specifications are subject to change without notice