

3.5 HDD DATA SHEET

The Power of Agility for Creative Pro and SME NAS Enclosures



IronWolf™ Pro is designed for everything business NAS. Get used to tough, ready and scalable 24x7 performance that can handle multi-drive environments across a wide range of capacities.



Best-Fit Applications

- 1- to 16-bay network attached storage (NAS)
- Backup, archiving and disaster recovery
- On-premise private cloud
- Virtual storage



Key Advantages

Optimised for NAS with AgileArray™. AgileArray enables dual-plane balancing and RAID optimisation in multi-bay environments, with the most advanced power management possible.

Actively protect your NAS with IronWolf Health Management focusing on prevention, intervention and recovery.¹

High performance means no lag time or downtime for users during workload traffic for the NAS. Seagate leads the competition with the highest-performing NAS drive portfolio.²

Seagate® Rescue Data Recovery.³ IronWolf Pro comes with extra peace of mind for any mechanical, accidental or natural disaster. With a 90% success rate of in-house recovery, Seagate has your back with a 2-year included Rescue Data Recovery plan.

Rotational Vibration (RV) sensors. First in its class of drives to include RV sensors to maintain high performance in multi-drive NAS enclosures.³

Range of capacities up to 12 TB. More capacity options means more choices that will fit within the budget. Seagate provides a scalable solution for any NAS use-case scenario.

Do more in multi-user environments. IronWolf provides a workload rate of 300 TB/year. Multiple users can confidently upload and download data to the NAS server, knowing IronWolf can handle the workload, whether you are a creative professional or a small business.

Designed for always on, always accessible 24x7 performance. Access data on your NAS any time, remotely or on site.

1.2 M hours MTBF, 5-year limited warranty represents an improved total cost of ownership (TCO) over desktop drives with reduced maintenance costs.

¹ Contact your Seagate sales representative for further information.

² Performance may vary depending on user's hardware configuration and operating system.

³ Registration required to activate. Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details.



Specifications	12 TB	10 TB	8 TB
Standard Model Number ¹	ST12000NE0007	ST10000NE0004	ST8000NE0004
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features			
Drive Bays Supported	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays
Multi-User Technology (TB/yr)	300	300	300
Rotational Vibration (RV) Sensors	Yes	Yes	Yes
Hot-Plug Support ²	Yes	Yes	Yes
Cache (MB)	256	256	256
Reliability/Data Integrity			
Mean Time Between Failures (MTBF, hours)	1,200,000	1,200,000	1,200,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%
Non-recoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8,760	8,760	8,760
Sector Size (Bytes per Logical Sector)	512E	512E	512E
Rescue Services ³	Yes	Yes	Yes
Limited Warranty (years)	5	5	5
Performance			
Spindle Speed (RPM)	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s)	250MB/s	214MB/s	214MB/s
Average Latency (ms)	4.16	4.16	4.16
Interface Ports	Single	Single	Single
Rotational Vibration @ 10-1,500 Hz (rad/s ²)	12.5	12.5	12.5
Power Consumption			
Startup Current, Typical (12V, A)	2	2	2
Idle Power, Average (W)	5.0	5.0	4.4
Average Operating Power (W)	7.8 W	7.8 W	7.4 W
Standby Mode (W)	0.8	0.8	0.8
Sleep Mode (W)	0.8	0.8	0.8
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
Environmental/Temperature			
Operating (ambient, min °C)	5	5	5
Operating (drive case, max °C)	60	60	60
Non-operating (ambient, min °C)	-40	-40	-40
Non-operating (ambient max °C)	70	70	70
Environmental/Acoustics			
Vibration, Non-operating: 10 Hz to 500 Hz (Grms)	2.27	2.27	2.27
Environmental/Shock			
Shock, Operating 2 ms (Read/Write) (Gs)	70/40 Gs	70/40 Gs	70/40 Gs
Shock, Non-operating, 1 ms and 2 ms (Gs)	250	250	250
Physical			
Height (mm/in)	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in
Width (mm/in, max)	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in
Weight (lb/g)	705 g/1.55 lb	705 g/1.55 lb	650 g/1.43 lb
Carton Unit Quantity	20	20	20
Cartons per Pallet / Cartons per Layer	40/8	40/8	40/8

¹ 2 TB and 4 TB models coming soon. For immediate needs, please see Enterprise NAS HDD.

² Supports Hotplug operation per Serial ATA Revision 2.6 specification.

³ Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.



Specifications	6 TB	4 TB	2 TB
Standard Model Number ¹	ST6000NE0023	ST4000NE0025	ST2000NE0025
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features			
Drive Bays Supported	Up to 16 Bays	Up to 16 Bays	Up to 16 Bays
Multi-User Technology (TB/yr)	300	300	300
Rotational Vibration (RV) Sensors	Yes	Yes	Yes
Hot-Plug Support ²	Yes	Yes	Yes
Cache (MB)	256	128	128
Reliability/Data Integrity			
Mean Time Between Failures (MTBF, hours)	1,200,000	1,200,000	1,200,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%
Non-recoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8,760	8,760	8,760
Sector Size (Bytes per Logical Sector)	512E	512E	512E
Rescue Services ³	Yes	Yes	Yes
Limited Warranty (years)	5	5	5
Performance			
Spindle Speed (RPM)	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s)	214MB/s	214MB/s	195MB/s
Average Latency (ms)	4.16	4.16	4.16
Interface Ports	Single	Single	Single
Rotational Vibration @ 10-1,500 Hz (rad/s ²)	12.5	12.5	12.5
Power Consumption			
Startup Current, Typical (12V, A)	2	2	2
Idle Power, Average (W)	7.5	5.45	4.61
Average Operating Power (W)	8.1 W	8.5 W	6.5 W
Standby Mode (W)	0.6	0.6	0.8
Sleep Mode (W)	0.6	0.6	0.8
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
Environmental/Temperature			
Operating (ambient, min °C)	5	5	5
Operating (drive case, max °C)	60	60	60
Non-operating (ambient, min °C)	-40	-40	-40
Non-operating (ambient max °C)	70	70	70
Environmental/Acoustics			
Vibration, Non-operating: 10 Hz to 500 Hz (Grms)	3	3	3
Environmental/Shock			
Shock, Operating 2 ms (Read/Write) (Gs)	70/40 Gs	70/40 Gs	70/40 Gs
Shock, Non-operating, 1 ms and 2 ms (Gs)	250	300	300
Physical			
Height (mm/in)	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in
Width (mm/in, max)	101.85 mm/4.01 in	101.85 mm/4.01 in	101.85 mm/4.01 in
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in
Weight (lb/g)	705 g/1.55 lb	680 g/1.5 lb	550 g/1.21 lb
Carton Unit Quantity	20	20	20
Cartons per Pallet / Cartons per Layer	40/8	40/8	40/8

¹ 2 TB and 4 TB models coming soon. For immediate needs, please see Enterprise NAS HDD.

² Supports Hotplug operation per Serial ATA Revision 2.6 specification.

³ Rescue recovery services not available in all countries. Contact your Seagate sales representative for further details. Register an IronWolf Pro drive to activate your 2-year Rescue plan at seagate.com/register.

AMERICAS	Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA	Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AgileArray and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1914.6-1708 GB August 2017