

Specifications

Instant Film	Fujifilm Instant Color Film "instax® WIDE"
Film size	86 x 108mm
Picture size	62 x 99mm
Lens	Retractable lens, 2 components, 2 elements, f = 95 mm, 1:14
Viewfinder	Advanced optical viewfinder, 0.37 x, with target spot
Focusing	Motor-driven 2-range switching (0.9m - 3m / 3m - ∞) Normal Mode (0.9m - 3m) Landscape Mode (3m - ∞)
Shutter Release	Programmed electronic shutter release, 1/64 sec - 1/200 sec.
Exposure control	Automatic, Interlocking range (ISO 800) : LV 10.5 - LV 15 Exposure compensation (Lighten-Darken Control) : ± 2/3EV
Film Feeding Out	Automatic
Flash	Built-in, automatic electronic flash, Charging time: 0.2 sec - 6 sec (using a new battery), Flash charging indicator (LED lights in red), Fill-in Flash Mode, Effective flash lamp range: 0.9m - 3m
Liquid Crystal Display (LCD)	Exposure counter (number of unexposed films), Lighten-Darken control, Fill-in Flash Mode
Power Supply	Four size AA 1.5 V alkaline batteries (LR6), Capacity : 10 film packs (Based on our test conditions)
Others	With film pack confirmation window, close up lens, and tripod socket included
Dimensions & Weight	167.8mm x 94.7mm x 120.9mm (not including protrusions) / 612g (without battery, strap, film pack, and close up lens)