

Audio-Technica AT-LP120-USB Direct-Drive P

SPECIFICATIONS

Type	3-speed, fully manual operation
Motor	DC motor
Drive Method	Direct drive
Speeds	33-1/3 RPM, 45 RPM, 78 RPM
Pitch Variation	+/-10% or +/-20%
Turntable Platter	Die-cast aluminum
Starting Torque	>1.6 kgf-cm
Braking System	Electronic brake
Wow and Flutter	<0.2% WRMS (33 RPM)
Signal-to-Noise Ratio	>50 dB
Output Level	Pre-amp "PHONO": 2.5 mV nominal at 1 kHz, 5 cm/sec Pre-amp "LINE": 150 mV nominal at 1 kHz, 5 cm/sec
Phono Pre-Amp Gain	36 dB nominal, RIAA equalized
USB Function	A/D, D/A - 16 bit 44.1 kHz or 48 kHz USB selectable; Computer interface - USB 1.1 Compliant Windows XP, Vista or MAC OS X
Power Supply Requirement	115/230V AC, 60/50 Hz
Power Consumption	11W
Dimensions	450.0 mm (17.72") W x 352.0 mm (13.86") D x 157.0 mm (6.1") H
Weight	10.7 kg (23.5 lbs.)
Accessories Included	Headshell/cartridge; AC line cord; dual RCA (female) to 3.5 mm (1/8") mini-plug (

Please note: As of September 2011, the AT-LP120-USB includes the AT95E cartridge, replacing the A

rofessional Turntable in Silver

male) stereo adapter cable; dual RCA (female) to 3.5 mm (1/8") mini-plug (female) stereo adapter cable;

TP-2XN cartridge.

; 45 RPM adapter; USB cable; recording software