

	<b>Model</b>	<b>RLC-422 (5MP Version)</b>
<b>Camera</b>	<b>Image Sensor</b>	1/2.9" CMOS Sensor
	<b>Effective Pixels</b>	3072 x 1728 (5.0 Megapixel)
	<b>Lens</b>	f=2.7-12mm Auto-focus, F=1.6
	<b>Angle of View</b>	Horizontal: 98° ~ 33°, Vertical: 54° ~ 22°
	<b>Day/Night Mode</b>	Auto Switchover
	<b>Min. Illumination</b>	0 Lux (With IR Illuminator)
	<b>IR Distance</b>	30 Meters
	<b>Backlight</b>	Support
	<b>Noise Reduction</b>	3D DNR
<b>Video</b>	<b>Compression</b>	H.264
	<b>Resolution</b>	Main Stream: 3072x1728, 2592x1944, 2560x1440, 2048x1536, 2304x1296; Sub Stream: 640 x 360
	<b>Bitrate</b>	Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps
	<b>Frame Rate</b>	PAL: Main Stream@20fps, Sub Stream@12fps; NTSC: Main Stream@20fps, Sub Stream@15fps
<b>Network</b>	<b>Interface</b>	One 10M/100Mbps RJ45
	<b>Network Protocol</b>	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, ONVIF, P2P
	<b>Browser Supported</b>	IE, Edge, Chrome, Firefox, Safari
	<b>OS Supported</b>	PC: Windows, Mac OS; Smart Phone: iOS, Android
	<b>Max. User Access</b>	20 Users
	<b>Storage</b>	Built-in Micro SD card socket (Maximum support of 64GByte); support motion detect record
<b>General</b>	<b>Power Supply</b>	DC 12V & PoE 48V (IEEE 802.3af)
	<b>Power Consumption</b>	<10W
	<b>Working</b>	-10°C~+55°C(14°F~131°F), 10%~90%
	<b>Ingress Protection</b>	IP66
	<b>Dimensions</b>	Φ133 x 100mm
	<b>Weight</b>	720g