

Specifications

Attributes	
Amperage	15.0
Bevel Angle Range	47° left and 47° right
Bevel Stops	0°, 33.9°, 45° and 47° (L/R)
Blade Diameter	10.0
Blade Size	10"
Case Type	No Case Included
Category	Compound Miter Saws
Depth Front-to-Back, Not Including Arm - In.	30.0
Dust Collection	Yes
Electric Motor Brake	Yes
Height	20.5"
Length	32.0"
Max. Base Molding Against Fence	3-1/4" (5-1/2" 0° to 47° L)
Max. Crown Molding (38° Spring) Angled Against Fence	5-1/4"
Max. Crown Molding (45° Spring) Angled Against Fence	6"
Max. Cut Capacity - 0° Miter 0° Bevel	3-1/8 In. x 12 In. (Can cut 4x12 dimensional lumber when Adjustable Depth Stop is used.)
Max. Cut Capacity - 0° Miter 45° Left Bevel	1-1/2 In. x 12 In. (Can cut 2x12 dimensional lumber)
Max. Cut Capacity - 0° Miter 45° Right Bevel	1 In. x 12 In. (Can cut 1x12 dimensional lumber)
Max. Cut Capacity - 45° Miter 0° Bevel	3-1/8 In. x 8 In. (Can cut 4x8 dimensional lumber when Adjustable Depth Stop is used.)
Max. Cut Capacity - 45° Miter 45° Left Bevel	1-1/2 In. x 8 In. (Can cut 2x8 dimensional lumber)
Max. Cut Capacity - 45° Miter 45° Right Bevel	1 In. x 8 In. (Can cut 1x8 dimensional lumber)
Miter Angle Range	52° Left, 60° Right
Miter Detents	0°, 15°, 22.5°, 31.6°, 45°, (Left/Right) 60°, (Right)
Miter Positive Stops	0°, 15°, 22.5°, 31.6°, 45° (Left/Right), 60° (Right)
No Load RPM	4,800

Attributes	
Separate On/Off Speed Control	Blank
Table Height from Base Feet to Table Surface - In.	4.0
Voltage	120V
Weight	64.0lb
Width	26.5"
Includes	(1) 10 In. 60-Tooth Carbide-Tipped Saw Blade, (1) Wrench, (1) Work Clamp, (1) Dust Bag, (1) Vacuum adapter/elbow