

SLASH (#58024) SPECS

Length	22.36 inches (568mm)
Front Track	11.65 inches (296mm)
Rear Track	11.65 inches (296mm)
Weight	76.2oz (2.16kg)
Height (overall)	8.425 inches (214mm)
Wheelbase	13.2 inches (335mm)
Front Shock Length	Long
Rear Shock Length	XXLong
Front Tires	Slash 2.2"
Rear Tires	Slash 2.2"
Front Wheels	2.2" Satin-Finish
Rear Wheels	2.2" Satin-Finish
Speed Control Type	Waterproof XL-5 ESC with low-voltage detection
Motor (electric)	Titan® 12T 550 (12-turn)
Gear Ratio (internal)	2.72 (final drive: 12.58)
Differential Type	Steel Composite Planetary
Gear Pitch	48-Pitch
Transmission	Metal Gear Magnum 272™
Steering	Bellcrank
Chassis Type	Modified Tub
Chassis Material	Composite Nylon
Center Ground Clearance	3.5 inches (89mm)
Top Speed	30+mph**
Skill Level	1
Radio System	TQ™ 2.4GHz Radio System (2-channel)

*Battery Tray Dimensions: 165mm x 49.5mm x 23mm, 25mm
Required Batteries 4 "AA" (transmitter), Traxxas Power
Cell Battery (7-cell NiMH or 2-cell LiPo)

*Battery expansion kit available (#5827X).

**With 7-cell battery and included optional 23-tooth pinion gear.

XL-5 (WATERPROOF) ESC SPECIFICATIONS

Input voltage:	4-7 Cells NiMH, 2-Cell (2S) LiPo
Case Size:	1.23"W x 2.18"D x 0.61" H
Weight:	2.44 Ounce
Motor Limit:	15-turns** (540 Size) 12-turns** (550 Size)
On Resistance Forward:	0.007 Ohms
On Resistance Reverse:	0.014 Ohms
Peak Current - Forward:	100A
Peak Current - Reverse:	60A
Braking Current:	60A
Continuous Current:	14A
BEC Voltage:	6.0 VDC
BEC Current:	1A
Power Wire:	14 Gauge / 5"
Input Harness Wire:	26 Gauge / 9"
Transistor Type:	MOSFET
PWM Frequency:	1600 Hz
Low Voltage Detection (LVD):	2-Stage indicators, switchable (on or off)
Thermal Protection:	Thermal shutdown
	Sport Mode:
Profile selection:	100% FWD, 100% brakes, 100% REV
	Race Mode:

100% FWD, 100% brakes, no REV
Training Mode:*
50% FWD, 100% brakes, 50% REV
Yes, Traxxas EZ-Set®

Single-button setup:



MODEL 58024: Fully assembled, Ready-To-Race®, with TQ™ 2.4GHz radio system, waterproof XL-5 Electronic Speed Control, Titan 12-turn motor, and ProGraphix® painted body.