

RØDELink Filmmaker Kit Specifications

Transmission type	2.4GHz Fixed Frequency Agile System
System dynamic range	112dB
Range (distance)	Up To 100m
Frequency range	35Hz - 22kHz
Maximum output level	1v Rms (2.8v P-p)
Max input signal level	1v Rms (2.8v P-p)
Max latency	4ms

Receiver (RX-CAM)

Power source	2 X AA Battery Or MicroUSB
Antenna	Internal
Output connection	3.5mm TRS Locking Jack Socket - Dual Mono
Output impedance	300Ω
Dimensions	111mm X 65mm X 52mm
Weight	190gm

Transmitter (TX-BELT)

Power source	2 X AA Battery Or MicroUSB
Antenna	Internal
Input connection	3.5mm TRS Locking Jack Socket
Input impedance	10kΩ
Dimensions	111mm X 65mm X 40mm
Weight	190gm

Lavalier

Acoustic Principle	Permanently Polarized
Active Electronics	JFET impedance converter
Capsule	0.10"
Address Type	End
Frequency Range	60Hz - 18kHz
Output Impedance	3000Ω
Maximum SPL	110dB SPL
Maximum Output Level	189.0mV
Sensitivity	-33.5dB re 1 Volt/Pascal (21.00mV @ 94 dB SPL) +/- 2 dB @ 1kHz
Equivalent Noise Level (A-weighted)	25dB-A
Weight	1.00gm
Dimensions	12.00mmH x 4.50mmW x 4.50mmD