

RT-AC68U

- Network Standard

IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IPv4, IPv6

- Product Segment

AC1900 ultimate AC performance : 600+1300 Mbps

- Coverage

Large homes

- Data Rate

802.11n : up to 450 Mbps

802.11n TurboQAM : up to 600 Mbps

802.11ac : up to 1300 Mbps

- Antenna

External antenna x 3

- Transmit/Receive

MIMO technology

2.4 GHz 3 x 3

5 GHz-1 3 x 3

- Memory

128 MB Flash

256 MB RAM

- Operating Frequency

2.4 GHz / 5 GHz

- Encryption

64-bit WEP, 128-bit WEP, WPA2-PSK, WPA-PSK, WPA-Enterprise , WPA2-Enterprise , WPS support

- Firewall & Access Control

Firewall : SPI intrusion detection, DoS protection

Access control : Parental control, Network service filter, URL filter, Port filter

- Management

UPnP, IGMP v1/v2/v3, DNS Proxy, DHCP, NTP Client, DDNS, Port Trigger, Universal Repeater, System Event Log

- WAN Connection Type

Internet connection type : Automatic IP, Static IP, PPPoE(MPPE supported), PPTP, L2TP

Multicast Proxy support

Multicast Rate Setting support

- Ports

RJ45 for 10/100/1000/Gigabits BaseT for LAN x 4, RJ45 for 10/100/1000/Gigabits BaseT for WAN x 1

USB 2.0 x 1

USB 3.0 x 1

- Button

WPS Button, Reset Button, Power Button, Wireless on/off Button

- Features

Airtime Fairness

Adaptive QoS

AiProtection

Parental Control

Guest Network : 2.4 GHz x 3, 5 GHz x 3

VPN server : IPSec Pass-Through, PPTP Pass-Through, L2TP Pass-Through, PPTP Server, OpenVPN Server

VPN client : PPTP client, L2TP client, OpenVPN client

Mac OS Backup

Enhanced media server (AiPlayer app compatible)

- Image : Jpeg

- Audio : mp3, wma, wav, pcm, mp4, lpcm, ogg

- Video : asf, avi, divx, mpeg, mpg, ts, vob, wmv, mkv, mov

AiCloud personal cloud service

3G/4G data sharing

Printer Server

- Multifunctional printer support (Windows only)
- LPR protocol support

Download Master

- Support bt, nzb, http, ed2k
- Support encryption, DHT, PEX and magnet link
- Upload and download bandwidth control
- Download scheduling

AiDisk file server

- Samba and FTP server with account management

Dual WAN

IPTV support

Roaming Assist

- LED Indicator

Power x 1
Wi-Fi x 2
LAN x 4
WAN x 1
USB x 2

- Power Supply

AC Input : 110V~240V(50~60Hz)
DC Output : 19 V with max. 1.75 A current

- OS Support

Windows® 10
Windows® 8.1
Windows® 8
Windows® 7
Windows® Vista
Windows® 2000
Windows® ME
Windows® XP
Windows® Server 2003
Windows® Server 2008
Mac OS X 10.1
Mac OS X 10.4
Mac OS X 10.5
Mac OS X 10.6
Mac OS X 10.7
Mac OS X 10.8
Mac OS X

Linux Kernel (Support Ubuntu only)
Linux

- Dimensions

220 x 83.3 x 160 ~ mm (WxDxH) (Without Bezel)

- Weight
- Package Content

1 x RT-AC68U Wireless-AC1900 Dual Band Gigabit Router
1 x RJ-45 cable
1 x Power adapter
1 x QSG
1 x Support CD(user manual and utility)

- Operation mode

Wireless router mode
Range extender mode
Access point mode
Media bridge mode