

Tech Specs

At a glance

- Drivers: 50 mm, with Neodymium magnets
- Connection type: Analog 3.5 mm
- Ultra-durable Kevlar™ reinforced cable
- Oval ear cushions: Designed for full-ear coverage, perfect for long-wearing comfort
- Microphone quick mute toggle

Headphones

- Frequency response: 12 Hz – 28 kHz
- Impedance: 32 Ω @ 1 kHz
- Sensitivity (@1 kHz): 118 dB
- Input power: 30 mW (Max)
- Drivers: 50 mm, with Neodymium magnets
- Inner ear cup diameter: 56 mm / 2.2 in
- Connection type: Analog 3.5 mm
- Ultra-durable Kevlar™ reinforced cable
- Cable length: 1.3 m / 4.27 ft. plus 2 m / 6.6 ft mic splitter adapter cable
- Approx. weight: 322 g / 0.71 lbs
- Oval ear cushions: Designed for full-ear coverage, perfect for long-wearing comfort

Microphone

- Frequency response: 100 Hz – 10 kHz
- Signal-to-noise ratio: > 55 dB
- Sensitivity (@1 kHz): -38 ± 3 dB
- Pick-up pattern: Unidirectional ECM boom

In-line control

- Analog volume control wheel
- Microphone quick mute toggle

Audio usage

- Devices with 3.5 mm audio jack

Audio + microphone usage

- Devices with 3.5 mm audio + mic combined