

Specs/Models	Standard Edition	Professional Edition	Professional Two-line Edition	Ultimate Two-line Edition
<b>Models</b>	A5 / B5 / C5	H5	T5	W5
<b>Storage</b> ◇	256MB/1GB/2GB	4GB	8GB	16GB
<b>Users</b> △	5/10/2020	100	200	400
<b>Fax Speed</b> ▲	14.4 kbps	33.6 kbps		
<b>Resolution</b>	98/196DPI			
<b>Caller Identification Format</b>	DTMF, FSK			
<b>Power Specification</b>	12V AC/DC			
<b>Power Consumption</b>	4W	5W	6W	
<b>LAN Port</b>	10M/100M Adaptive Ethernet RJ45×2 ( works as a switch,connects to the computer )			
<b>Line Port</b>	1 Line		Each server supports 2 lines. Servers bound support up to 1024 lines	
<b>Dimension</b>	18×10.5×3 cm	19×25×6 cm		
<b>Weight</b>	0.495KG	1.2KG	1.3KG	
<b>Ambient Temperature</b>	0°C ~ 40°C			
<b>Ambient Moisture</b>	5% ~ 90% RH			
<b>Storage Temperature</b>	-40°C ~ 80°C			
<b>Fax to Email</b>	SMTP			
<b>Support OS</b>	WinXP/Win7/Win8/Win8.1/Win10 ( 32/64 Bit)			
<b>Digital Signature</b>	Seal on the perforation supported			
<b>Remote Access</b>	√			
<b>(Custom) IVR</b>	√			
<b>Email to Fax</b>				POP3
<b>SDK for Developers</b>				√
<b>Multiple Local Servers Binding</b>				√
<b>Multiple Distance Servers Binding</b>				√
◇ Storage is slightly affected by software editions.				
△ Number of users is stated on outer package.				
▲ Fax speed is subject to telephone line quality.				