

Package Contents

- 4-Way HDMI Switch
- Remote Control
- Infrared Extender/Receiver
- Quick Install Guide

IMPORTANT NOTE: POWER SUPPLY

When an HDMI cable is used with an HDMI device, this Switch will be powered by the 5V that always runs from a standard HDMI device through the cable.

If this Switch is connected to a non-HDMI device or connected to a long HDMI cable, there is a port on the Switch that will accept the necessary power supply. This power supply is not included and must be purchased separately.

Introduction

Congratulations and thank you for purchasing the Belkin 4-Way HDMI Switch with Wireless Remote.

This product allows you to connect and switch among four separate HD video sources and use only one HDMI connection on your HDTV. This allows easy switching between devices such as HD gaming systems, Blu-ray® players, and HD set-top boxes with a wireless remote. There is also an intelligent switching function, which detects the device that is powered on and automatically switches to that device.

Benefits

- Connect and switch among four HD video sources using only one HDMI connection on your HDTV
- Supports 480i, 480p, 720i, 720p, 1080i, and 1080p video resolutions
- Supports 3D signals
- Select connected devices from the IR remote control (supplied) or via the front-panel "Input Select" button
- LED indicator shows current source device

Installation

1. Place the 4-Way HDMI Switch away from heat, moisture, and sources of electromagnetic or radio frequency interference.
2. Connect HD source devices into the ports marked "Input 1, 2, or 3"
3. Connect the HDMI switchbox to the HDTV through the port marked "Output"
4. Plug the IR remote sensor through the small, round port on the side of the HDMI switchbox marked "IR."
5. Place the IR sensor in a visible place near the front of the product with clear access to remote control commands (length = 50cm)
6. When the power of the HD source is turned on, the HDMI Switch will automatically select that input to begin normal operation.

Remote Control

1. Press the "Input Select" button repeatedly until the desired input is selected.
2. Each press progresses to the next input in turn (i.e., 1-2-3, then back to 1).
3. The current input is identified by the lighted LED indicator on the front panel.



Specifications

Output Video	HDMI 1.3b
Maximum Single Link Range	1920x1080p
Frequency Range	50/60Hz
Video Amplifier Bandwidth	2.5Gbps/250MHz
Video Screen Resolutions	480i, 480p, 720i, 720p, 1080i, 1080p
Operating Temperature	0° C to +70° C
Operating Humidity	10% to 85% RH (no condensation)
Storage Temperature	-10° C to +80° C
Storage Humidity	5% to 90% RH (no condensation)
External Power Supply	No external power needed
IR Receiver	3.5mm stereo jack; 50cm cable length
Dimensions (L x W x H)	80mm x 58mm x 17mm
Warranty	Limited Lifetime Warranty

Optional Power Supply

Input DC Power	5 Volts
Power Consumption	5 Watts (max.)

Belkin Ltd.
Express Business Park
Shipton Way, Rushden
NN10 6GL, United Kingdom

Belkin B.V.
Tupolevlaan 1
1119 NW Schiphol-Rijk
Netherlands

Belkin International, Inc.
12045 E. Waterfront Drive
Playa Vista, CA 90094, USA

Belkin.com

© 2012 Belkin International, Inc. All rights reserved. All trade names are registered trademarks of respective manufacturers listed. HDMI is a trademark or registered trademark of HDMI Licensing LLC in the United States and other countries.

