

Model		RLC-422W
Camera	Image Sensor	1/2.9" CMOS Sensor
	Effective Pixels	3072 x 1728 (5.0 Megapixels)
	Lens	f=2.7-12mm Auto-focus, F=1.6
	Angle of View	Horizontal: 98° ~ 33°, Vertical: 54° ~ 22°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters
	Backlight	Support
	Noise Reduction	3D DNR
Video	Compression	H.264
	Resolution	Main Stream: 3072x1728, 2592x1944, 2560x1440, 2048x1536, 2304x1296; Sub Stream: 640 x 360
	Bitrate	Main Stream: 1024Kbps ~ 8192Kbps, Sub Stream: 64Kbps ~ 512Kbps
	Frame Rate	PAL: Main Stream@20fps, Sub Stream@12fps; NTSC: Main Stream@20fps, Sub Stream@15fps
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	HTTPS, SSL, TCP/IP, UDP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, DDNS, FTP, ONVIF, P2P
	Browser Supported	IE, Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smart Phone: iOS, Android
	Max. User Access	20 Users
	Storage	Built-in Micro SD card socket (Maximum support of 64GByte); support motion detect record
WiFi	Wireless Standard	IEEE 802.11a/b/g/n
	Operating	2.4GHz/5GHz
	Wireless Security	WPA-PSK/WPA2-PSK
General	Power Supply	DC12V
	Power Consumption	<10W
	Working	-10°C~+55°C (14°F~131°F), 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ133 x 100mm
	Weight	720g