

## Full Range of Model Specifications.

Chill comes in a range of sizes and capacities. Click on the model number for detailed installation information. Take a look.

### Chill

<b>CP05G10B</b>	5200	n/a	11.2	11	115v	No	12 5/16"	18 9/16"	15 7/16"
<b>CP06G10B</b>	6000	n/a	12.2	12.1	115v	Yes	13 7/8"	18 9/16"	20 11/16"
<b>CP08G10B</b>	8000	n/a	12.2	12	115v	Yes	13 7/8"	18 9/16"	20 11/16"
<b>CP10G10B</b>	10000	n/a	12.1	12	115v	Yes	15"	23 5/8"	22 1/16"
<b>CP12G10B</b>	12000	n/a	12.1	12	115v	Yes	15"	23 5/8"	22 1/16"
<b>CP15G10B</b>	15500	n/a	11.9	11.8	115v	Yes	16 7/8"	25 1/2"	30 5/16"
<b>CP18G30B</b>	19000/ 18600	n/a	11.9/ 11.9	11.8/ 11.8	230/ 208v	Yes	16 7/8"	25 1/2"	30 5/16"
<b>CP24G30B</b>	24000/ 23500	n/a	10.4/ 10.4	10.3/ 10.3	230/ 208v	Yes	16 7/8"	25 1/2"	30 5/16"

### Chill + Electric Heat

<b>EP08G11B</b>	7500	3850	11.2	11	115v	n/a	13 7/8"	18 9/16"	20 11/16"
<b>EP12G33B</b>	12000/ 11500	11200/ 9200	11.3/ 11.3	11.2/ 11.2	230/ 208v	n/a	15"	23 5/8"	22 1/16"
<b>EP18G33B</b>	18000/ 17500	12000/ 9800	11.2/ 11.2	11.1/ 11.1	230/ 208v	n/a	16 7/8"	25 1/2"	30 5/16"
<b>EP24G33B</b>	23000/ 22500	12000/ 9800	9.8/ 9.8	9.8/ 9.8	230/ 208v	n/a	16 7/8"	25 1/2"	30 5/16"

## Room Sizing Guide

FT <sup>2</sup>	BTU
100–150	5000
150-250	6000
250-300	7000
300–350	8000
350–400	9000
400–450	10000
450-550	12000
550-700	15000
700–1000	18000
1000-1200	21000
1200-1400	23000
1400–1600	25000
1600–1900	28000
1900–2700	36000

This guide is based on normal room insulation, average number of sun-exposed windows and two-person occupancy.