

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Thermally Conductive Epoxy: Encapsulating and Potting Compound (Part A)

SDS Code: 832TC-Part A

Related Part # 832TC-450ML, 832TC-2L, 832TC-8L, 832TC-40L

Recommended Use and Restriction on Use

Use: Thermally conductive epoxy resin for use with hardeners

Uses Advised Against: Not applicable

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772

FAX +1-800-340-0773

E-MAIL support@mgchemicals.com

WEB www.mgchemicals.com

☎ +1-905-331-1396

FAX +1-905-331-2682

E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents

USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7

CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Reproductive Toxicity		1B	Danger	Health
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	2	none	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H360: May damage fertility or the unborn child
	H319: Causes serious eye irritation H317: May cause an allergic skin reaction H315: Causes skin irritation
	H411: Toxic to aquatic life with long lasting effects

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Continued ...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201 + P202	Obtain special instructions before use. Do not handle until all safety precautions have been understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P261	Avoid breathing fumes/vapors.
P264	Wash hands and exposed skin thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection.
P273	Avoid release to the environment.
Response	Precautionary Statements
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

THERMALLY CONDUCTIVE EPOXY
832TC-PART A
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
28064-14-4	phenyl glycidyl ether/ formaldehyde copolymer	48%
1344-28-1	aluminium oxide	47%
25068-38-6	bisphenol-A epoxy resin (reaction product)	2%
64741-65-7	naphtha, petroleum, heavy alkylate	1%
1333-86-4	carbon black	0.7%
68609-97-2	alkyl glycidyl ether	0.5%
872-50-4	1-methyl-2-pyrrolidone	0.1%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
Response	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340, P312, P308 + P313
Immediate Symptoms	<i>cough, irritation of the respiratory track</i>
Response	Remove person to fresh air and keep comfortable for breathing. If you feel unwell: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>irritation</i>
Response	Rinse mouth. Do NOT induce vomiting.

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****Section 5: Fire-Fighting Measures**

Extinguishing Media	Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂) and toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the fumes/vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash residue with a paper towel wetted with alcohol, ethyl lactate, or another suitable organic solvent; and place dirty towels in container. Use soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Section 7: Handling and Storage

- Prevention** Keep out of reach of children.
- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
- Avoid breathing fumes/vapors or contact with skin or eyes.
- Avoid release to the environment.
- Handling** Wear protective gloves/protective clothing/eye protection.
- Contaminated work clothing should not be allowed out of the workplace.
- Take off contaminated clothing and wash it before reuse.
- Wash hands thoroughly after handling.
- Collect spillage.
- Storage** Store locked up.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum oxide ^{a)}	ACGIH	1 mg/m ³	Not established
	U.S.A. OSHA PEL	15 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	1 mg/m ³	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	10 mg/m ³	Not established
naphtha, petroleum, heavy distillate	ACGIH	100 ppm (525 mg/m ³)	Not established
	U.S.A. OSHA PEL	500 ppm (2 900 mg/m ³)	Not established
	Canada AB	572 mg/m ³	Not established
	Canada BC	290 mg/m ³	580 mg/m ³
	Canada ON	100 ppm	Not established
	Canada QC	525 mg/m ³	Not established

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Continued...

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
carbon black ^{a)}	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established
1-methyl-2-pyrrolidinone	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	400 mg/m ³	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Because the carbon black and aluminum oxide are bound to the liquid mixture, they do not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

Recommendation: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

Not normally required, but if exposed to high levels of mist/vapors/fumes, wear respirator such as a half-mask respirator with organic vapor cartridge.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

THERMALLY CONDUCTIVE EPOXY
832TC-PART A
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black	Upper Flammability Limit	Not available
Odor	Mild aromatic	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	>1 (Air = 1)
pH	Not available	Specific Gravity @25 °C	1.73
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Boiling Point	>150 °C [>302 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	150 °C [302 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @25 °C	36 000 cP

a) The closed cup flash point for component with the lowest reported value.

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with amines.
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Excessive heat, and incompatible substances. Do not use in a way that forms a mist or aerosolize the product.
Incompatibilities	Strong oxidizing agents, strong bases, strong acids, halogenated hydrocarbons
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

THERMALLY CONDUCTIVE EPOXY
832TC-PART A
Section 11: Toxicological Information
Routes of Exposure

Skin contact, Ingestion, Inhalation, and Eye contact

Symptoms Summary

Eyes	May cause eye redness, irritation, or pain.
Skin	May cause skin redness, irritation, dry skin, or allergic contact dermatitis.
Inhalation	Inhalation of vapors or fumes may cause irritation to the nose, throat and lung (upper respiratory tract).
Ingestion	May cause irritation. Also see inhalation symptoms.
Chronic	Prolonged or repeated exposure to the uncured epoxy resins used may cause dermatitis and sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
phenyl glycidyl ether/ formaldehyde copolymer	4 000 mg/kg Rabbit ^{a)}	Not established	6 000 mg/kg Rabbit ^{a)}
aluminum oxide	Not established	Not established	Not established
bisphenol-A-(epichlorhydrin)	15 000 mg/kg Rat	23 000 mg/kg 7 h Rabbit ^{a)}	Not established
carbon black	>15 g/kg Rat	>3 g/kg Rabbit	Not established
alkyl glycidyl ether	19 200 mg/kg Rat ^{a)}	4 500 mg/kg Rat ^{a)}	Not established
1-methyl-2-pyrrolidone	3 914 mg/kg Rat	>2 000 mg/kg Rabbit	Not established

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier (M)SDS were also consulted.

a) Supplier MSDS

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****Other Toxicological Effects**

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Sensitization (allergic reactions)	The epoxy resin components (CAS# 28064-14-4, 25068-38-6, and 68609-97-2) may cause skin sensitization in humans.
Carcinogenicity (risk of cancer)	<p>The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures under WHMIS.</p> <p>Because the carbon black is bound in the epoxy liquid mixture, it is not available as an airborne hazard (dust, mist, or spray) under normal use.</p> <p>Carbon Black [1333-86-4]</p> <p>IARC Group 2B: Possibly carcinogenic to humans</p> <p>ACGIH A4: Not classified as a human carcinogen</p> <p>CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)</p> <p>NTP: Not listed</p>
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	<p>At large doses of >4 000 mg/kg, 1-methyl-2-pyrrolidone shows reproductive effects based on studies in rats and mice.</p> <p>1-Methyl-2-pyrrolidone [CAS# 872-50-4]</p> <p>CA Prop 65: Listed as a reproductive toxicant.</p>
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There is <10% components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

In Europe, similar epoxy resins with CAS# 28064-14-4 are generally classified as category 2 marine pollutants due to a LC50 96 h of >1 mg/L but ≤10 mg/L. Chronic toxic effects have been suggested.

The 1-methyl-2-pyrrolidinone ingredient is not classified as an environmental hazard according to GHS criteria with minimal LC50 96 h of >500 mg/L for Pimephales promelas (fathead minnow); EC50 24 h of ≥1 000 mg/L Daphnia pulex (water flea).

Based on available data, carbon black and alkyl glycidyl ether is not classified as environmental hazard according to GHS criteria.

Acute Ecotoxicity

See chronic ecotoxicity.

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage

Biodegradability

The content is not readily biodegradable.

Bioaccumulation

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes under 450 L

Part A of all 832TC kits

NOT REGULATED in TDG
per Special Provisions 99

49 CFR: Sizes greater than 5 L


Part A of 832TC-40L kit

UN number: UN3082

Shipping Name:

ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S.

(Reaction product: bisphenol-A-
(epichlorhydrin))



Sizes 5 L and under

*Part A of 832TC-450ML, 832TC-2L,
832TC-8L kits*

NOT REGULATED in 49 CFR
per exception 171.4 (c)(2)

Class: 9

Packing Group: III

Marine Pollutant: Yes



Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****Air****Refer to ICAO-IATA Dangerous Goods Regulations.****Sizes 5 L and under:***Part A of 832TC-450ML, 832TC-2L,
832TC-8L kits***NOT REGULATED**On air waybill write:
"Not Restricted, as per
Special Provisions A197"**Sizes greater than 5 L:***Part A of 832TC-40L kit***UN number:** UN3082**Shipping Name:**
ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S.
(Reaction product: bisphenol-A-
(epichlorhydrin))**Class:** 9**Packing Group:** III**Marine Pollutant:** Yes**Special Provision A197:** These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.*Section continued on the next page*

THERMALLY CONDUCTIVE EPOXY

832TC-PART A

Sea

Refer to IMDG regulations.

Sizes 5 L and under:

Part A of 832TC-450ML, 832TC-2L, 832TC-8L kits

NOT REGULATED

per 2.10.2.7

Sizes greater than 5 L:

Part A of 832TC-40L kit

UN number: UN3082

Shipping Name:
ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S.
(Reaction product: bisphenol-A-
(epichlorhydrin))

Class: 9

Packing Group: III

Marine Pollutant: Yes



2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.


Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****USA****Other Classifications****HMIS® RATING**

HEALTH:	* 3
FLAMMABILITY:	2
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

This product contains 1-methyl-2-pyrrolidone, listed as a developmental reproductive toxicant.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

THERMALLY CONDUCTIVE EPOXY**832TC-PART A****Section 16: Other Information****SDS Prepared by** Michel Hachey**Date of Review** 14 November 2016**Supersedes** 09 August 2016**Reason for Changes:** Change to California Proposition 65 statement in section 15.**Reference**

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART A**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

THERMALLY CONDUCTIVE EPOXY

832TC-PART B

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Thermally Conductive Epoxy: Encapsulating and Potting Compound (Part B)

SDS Code: 832TC-Part B

Related Part # 832TC-450ML, 832TC-2L, 832TC-8L, 832TC-40L

Recommended Use and Restriction on Use

Use: Thermally conductive epoxy resin for use with hardeners to pot devices or encapsulate components

Uses Advised Against: Not applicable

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772
FAX +1-800-340-0773
E-MAIL support@mgchemicals.com
WEB www.mgchemicals.com

☎ +1-905-331-1396
FAX +1-905-331-2682
E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents
USA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7
CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

THERMALLY CONDUCTIVE EPOXY
832TC-PART B
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Reproductive Toxicity	1B	Danger	Health
Sensitization Skin	1	Warning	Exclamation
Eye Irritation	2	Warning	Exclamation
Skin Irritation	2	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H360: May damage fertility or the unborn child
	H319: Causes serious eye irritation H317: May cause an allergic skin reaction H315: Causes skin irritation
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201 + P202	Obtain special instructions before use. Do not handle until all safety precautions have been understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P261	Avoid breathing fumes/vapors.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/eye protection.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY
832TC-PART B

Continued...

Response	Precautionary Statements
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
1344-28-1	aluminum oxide	52%
68071-65-8	modified polyamide polymer	30%
100-51-6	benzyl alcohol	11%
112-24-3	triethylenetetramine	2%
64741-65-7	naphtha, petroleum, heavy alkylate	1%
108-65-6	2-methoxy-1-methylethyl acetate	1%
1333-86-4	carbon black	0.6%
872-50-4	1-methyl-2-pyrrolidone	0.1%

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	<i>redness, irritation, dry skin, allergic contact dermatitis</i>
Response	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340, P308 + P313
Immediate Symptoms	<i>cough, irritation of the respiratory track,</i>
Response	Remove person to fresh air and keep comfortable for breathing IF exposed or concerned: Get medical advice/attention.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>irritation</i>
Response	Rinse mouth. Do not induce vomiting.

Advice to Physicians

In case of overexposure to nitrogen oxides (NO_x) combustion products or triethylenetetramine vapors during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Section 5: Fire-Fighting Measures**

Extinguishing Media	Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂), nitrogen oxides (NO _x), and toxic fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing fumes/vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash residue with a paper towel wetted with alcohol, ethyl lactate, or another suitable organic solvent; and place dirty towels in container. Use soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

THERMALLY CONDUCTIVE EPOXY
832TC-PART B
Section 7: Handling and Storage

Prevention	Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing fumes/vapors. Contaminated work clothing should not be allowed out of the workplace.
Handling	Wear protective gloves/clothing/eye protection. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling.
Storage	Store locked up.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum oxide ^{a)}	ACGIH	1 mg/m ³	Not established
	U.S.A. OSHA PEL	15 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	1 mg/m ³	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	10 mg/m ³	Not established
triethylenetetramine	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A (WEEL)	1 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	0.5 mg/m ³ (S)	Not established
naphtha, petroleum, heavy distillate	Canada QC	Not established	Not established
	ACGIH	100 ppm (525 mg/m ³)	Not established
	U.S.A. OSHA PEL	500 ppm (2 900 mg/m ³)	Not established
	Canada AB	572 mg/m ³	Not established
	Canada BC	290 mg/m ³	580 mg/m ³
Canada ON	100 ppm	Not established	
Canada QC	525 mg/m ³	Not established	

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY
832TC-PART B
Continued...

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
2-methoxy-1-methylethyl acetate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	50 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	75 ppm
	Canada ON	50 ppm	Not established
carbon black ^{a)}	Canada QC	Not established	Not established
	ACGIH	3.5 mg/m ³	Not established
	U.S.A. OSHA PEL	3.5 mg/m ³	Not established
	Canada AB	3.5 mg/m ³	Not established
	Canada BC	3 mg/m ³	Not established
1-methyl-2-pyrrolidinone	Canada ON	3.5 mg/m ³	Not established
	Canada QC	3.5 mg/m ³	Not established
	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	400 mg/m ³	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

(S) Skin—can be absorbed through the skin.

a) Respirable airborne particles

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Because the carbon black and aluminum oxide is bound to the liquid mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

Recommendation: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

Not normally required, but if exposed to high levels of mist/vapors/fumes, wear respirator such as a half-mask respirator with organic vapor cartridge.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

THERMALLY CONDUCTIVE EPOXY
832TC-PART B
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black	Upper Flammability Limit	Not available
Odor	Slight aromatic	Vapor Pressure^{b)} @20 °C	<0.1 kPa [<1 mmHg]
Odor Threshold	Not available	Vapor Density	>1 (Air = 1)
pH	Not available	Specific Gravity @25 °C	1.61
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Boiling Point	Not available	Partition Coefficient	Not available
Flash Point^{a)}	93 °C [199 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @25 °C	14 000 cP

a) The closed cup flash point for component with the lowest reported value

b) Based on supplier value of main hardener system

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with epoxides.
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Excessive heat, and incompatible substances. Do not use in a way that forms a mist or aerosolize the product.
Incompatibilities	Strong oxidizing agents, strong bases, strong acids, halogenated hydrocarbons
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

THERMALLY CONDUCTIVE EPOXY
832TC-PART B
Section 11: Toxicological Information
Routes of Exposure

Skin contact, Ingestion, Inhalation, and Eye contact

Symptoms Summary

Eyes	Causes serious eye irritation, redness and/or pain.
Skin	Causes skin redness, irritation, dry skin, or allergic contact dermatitis.
Inhalation	Inhalation of vapors or mist may cause irritation to the nose, throat and lung (upper respiratory tract). When heated, hot triethylenetetramine vapors may also result in itching of the face with skin redness (erythema) and swelling (edema).
Ingestion	<i>Not a likely route of exposure.</i> See skin and inhalations symptoms.
Chronic	Prolonged or repeated exposure to the uncured epoxy resins used may cause dermatitis and sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
aluminum oxide	Not established	Not established	Not established
modified polyamide polymer	Not established	Not established	Not established
benzyl alcohol	1 230 mg/kg Rat	2 000 mg/kg Rabbit	Not established
triethylenetetramine	2 500 mg/kg Rat	805 mg/kg Rabbit	Not established
naphtha, petroleum, heavy alkylate	Not established	Not established	Not established
2-methoxy-1-methylethyl acetate	8 532 mg/kg Rat	>5 g/kg Rabbit	Not established
1-methyl-2-pyrrolidone	3 914 mg/kg Rat	>2 000 mg/kg Rabbit	Not established

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier (M)SDS were also consulted.

a) Supplier MSDS

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Other Toxicological Effects**

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes severe eye irritation.
Sensitization (allergic reactions)	The triethylenetetramine may cause skin sensitization in humans
Carcinogenicity (risk of cancer)	<p>The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures under WHMIS.</p> <p>Because the carbon black is bound in the epoxy liquid mixture, it is not available as an airborne hazard (dust, mist, or spray) under normal use.</p> <p>Carbon Black [1333-86-4]</p> <p>IARC Group 2B: Possibly carcinogenic to humans</p> <p>ACGIH A4: Not classified as a human carcinogen</p> <p>CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)</p> <p>NTP: Not listed</p>
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	<p>At large doses of >4 000 mg/kg, 1-methyl-2-pyrrolidone shows reproductive effects based on studies in rats and mice.</p> <p>1-methyl-2-pyrrolidone [CAS# 872-50-4]</p> <p>CA Prop 65: Listed as a reproductive toxicant.</p>
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Literature for the triethylenetetramine (CAS # 112-24-3) suggest low aquatic toxicity (LC50, IC50, and EC50 values of >100 mg/L for fish and between 10 and 100 for algae).

The 1-methyl-2-pyrrolidinone ingredient is not classified as an environmental hazard according to GHS criteria with minimal LC50 96 h of >500 mg/L for Pimephales promelas (fathead minnow); EC50 24 h of $\geq 1\ 000$ mg/L Daphnia pulex (water flea).

Based on available data, aluminum oxide, modified polyamide polymer, benzyl alcohol, naphtha, petroleum, heavy alkylate, 2-methoxy-1-methylethyl acetate, carbon black, and 1-methyl-2-pyrrolidone are not classified as environmental hazard according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Not readily biodegradable.

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Section 14: Transport Information****Ground**

Refer to **TDG regulations** (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Non Regulated

Air

Refer to **ICAO-IATA Dangerous Goods Regulations.**

Non Regulated

Sea

Refer to **IMDG regulations.**

Non Regulated

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Section continued on the next page

THERMALLY CONDUCTIVE EPOXY

832TC-PART B


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

This product contains 1-methyl-2-pyrrolidone, listed as a developmental reproductive, toxicant.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

THERMALLY CONDUCTIVE EPOXY**832TC-PART B****Section 16: Other Information**

SDS Prepared by Michel Hachey
Date of Review 14 November 2016
Supersedes 11 August 2016

Reason for Changes: Change to California Proposition 65 statement in section 15.

Reference

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Section continued on the next page



Quality System Certified to ISO 9001:2008

SAI Global File #004008

Burlington, Ontario, Canada

THERMALLY CONDUCTIVE EPOXY

832TC-PART B

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.