

# LaView 8 Channel H.264 IP Network Video Recorder



## Key Features

- Third-Party network cameras supported
- Up to 6MP resolution recording
- HDMI and VGA output at up to 1920 x 1080P resolution
- Plug & Play with 8 independent PoE network interfaces
- 2 SATA HDD interface up to 6TB each
- HDD quota and group management

## Rear Panel

1. LAN Network Interface
2. 100-240VAC Power Input
3. Power Switch
4. USB Port
5. Ground
6. HDMI Interface
7. VGA
8. Audio In
9. Audio Out
10. Network Interfaces with PoE function



## LaView 8 Channel H.264 IP Network Video Recorder

NVR	LV-N9808C8E
<b>Video/Audio Input</b>	
IP video input	8-ch
Two-way audio input	1-ch, RCA(2.0Vp-p,1kΩ)
Incoming bandwidth	80Mbps
Outgoing bandwidth	80Mbps
Remote connections	128
<b>Video/Audio output</b>	
Recording resolution	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
HDMI/VGA output	1-ch, resolution: 1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60Hz
Frame Rate	Main Stream: 60 fps(N)/50 fps(P)
	Sub-stream: 60 fps(N)/50 fps(P)
Audio output	1-ch, RCA (Linear, 1 kΩ)
<b>Decoding</b>	
Playback resolution	6MP/5MP/4MP/3MP/1080P/UXGA / 720P / VGA / 4CIF / DCIF / 2 CIF / CIF / QCIF
Capability	8-ch
<b>Hard disk</b>	
SATA	2 SATA interface for 2 HDDs
Capacity	Up to 6TB capacity for each HDD
<b>External interface</b>	
Network interface	1 RJ-45 10M / 100M/1000M self-adaptive Ethernet interface
USB port	1 × USB2.0,1×USB3.0
<b>POE Interface</b>	
Interface	8 independent 100 Mbps PoE
Power	≤ 120W
Supported standard	AF/AT
<b>General</b>	
Power Supply	100 ~ 240 VAC, 47 ~ 63 Hz, 3A
Consumption	≤ 10 W
Working temperature	14° F~131° F(-10° C~+55° C)
Working humidity	10%~90%
Chassis	19-inch rack-mounted 1U chassis
Dimensions (WxDxH)	17.5" x 11.4" x 1.8" (445 x 290 x 45mm)
Weight	≤ 8.8lb(4kg)