

WaterSentinel®

WSW-5 REFRIGERATOR REPLACEMENT FILTER



ADVANCED FILTRATION TECHNOLOGY

This WaterSentinel® refrigerator water filter contains a compressed carbon block which provides tremendous capacity to remove and/or reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on its surface and within the structure which can absorb impurities like a sponge, and can adsorb and hold other types of impurities on its surface like a magnet. Additionally, this filter can catalytically breakdown other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.

This economical filter will provide you with fresh and clean tasting water and ice cubes.

THIS FILTER FITS IN PLACE OF:

Whirlpool® Filters:

FILTER3, FILTER3C, 4396710, 4396710B, 4396710P, 4396710T, 4396711B, 4396841, 4396841B, 4396841P, 4396841T, 4396842B, 4396842

Kenmore® Filters:

46-9020, 46-9020P, 46-9030, 46-9030P, 4609020000, 4609030000, 469020, 469020P, 469030, 469030P

PUR® Filters:

W10121145, W10121146, W10177635, W10186667, W10193691, W10193691T, 8212650, 95357630, AP3710633, AP3866834, F3WP6M1, P1KB1, P1KB2, P1RFKB1, P1RFKB2, P1RFBW2, P1RFBW2L, P1WB2, P1WB2L, P1WG2, P1WG2L, P2RFBW2, P2WG2, P2WG2L, PB-SS, PBSS, PS971185, PS986832, RWFFRSXS, T1KB1, T1KB2, T1RFKB1, T1RFKB2, T1RFBW2, T1RFBW2L, T1WB2, T1WB2L, T1WG2, T1WG2L, T2RFBW2, T2WG2, T2WG2L, 2260515, 2260538, 2305222, 2305267, 2313412, 2260518B, 2260518W

Guaranteed to fit by WaterSentinel®

FILTER FEATURES:

- Economical alternative to expensive substitutes
- Delivers clean, clear water that looks and tastes great
- Will remove or reduce chlorine taste and odor that may be present in your drinking water
- Designed to provide up to six months of life or 400 gallons
- Does not remove minerals which may be beneficial to health

SPECIFICATIONS:

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Min Operating Pressure:	30 psi (207 kPa)
Max Operating Pressure:	100 psi (689 kPa)
Life:	6 months or 240 gallons (900 liters)

*WHIRLPOOL IS A REGISTERED TRADEMARK OF WHIRLPOOL, U.S.A.

†KENMORE IS A REGISTERED TRADEMARK OF KCO LP, LLC.

‡PUR IS A TRADEMARK OF HELEN OF TROY LIMITED, AND USED UNDER LICENSE.



Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and/or after the system.



This WSW-5 is Tested and Certified by WQA against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.