

WGen7500

7500 Watt Open Frame Gasoline Portable Generator

7500 Running Watts | 9500 Peak Watts



Rugged roll bars for added strength and protection

Fuel gauge on top of 6.6 gal. tank



50 State and
Canada Model


Push button electric start,
lights up green when unit is on

Battery charging port
(charger included)

Westinghouse ST Switch outlet

Dependable 13 HP 420cc OHV
4-Stroke Westinghouse engine

Remote start key fob included
for starting and stopping
generator up to 109 yards away



What Comes in the Box



WGen7500

Generator Specifications



Gasoline Running Watts	7500
Gasoline Peak Watts	9500
Running Amps	31 amps
Peak Amps	39 amps
AC Voltage	120/240 Volts
AC Frequency	60 Hz
Engine Horse Power (HP)	13 HP
Total Harmonic Distortion (THD)	<23%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Electric, Remote, Recoil
Battery	Yes
Battery Charger Included	Yes
Remote Start Fob Included	Yes (factory paired)
Remote Start Distance (yards/meters)	109 yd. (100 m.)
Push Button Start	Yes
Mobile App Compatible	No
Engine Displacement	420cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine RPM	3600
Operational Volume (dBA)	73 dBA
Spark Plug (included)	Torch F7TC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140545
Auto Idle Control	No
Built-in Inverter	No
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	1.1 qt. (37.2 oz)
Oil Capacity (Quarts/Ounces)	1.1 qt. (37.2 oz)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, %10 Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Capacity (Gallons/Liters)	6.6 gal. (25 L)
Run Time at %25 Load (hrs.)	16 hrs.
Run Time at %50 Load (hrs.)	11 hrs.

Gasoline Fuel Gauge	Yes
Choke type	Automatic
Choke Location	Above Air Filter
AC Outlets	(1) 120/240V 30A (L14-30R) (2) Duplex 120V 20A GFCI (5-20R)
Ground	Neutral Bonded
Covered Outlets	Yes
Transfer Switch Ready	Yes
Westinghouse Portable Transfer Switch Ready (ST Switch)	Yes
GFCI Outlets	Yes
VFT Data Center (volts, frequency, lifetime hours)	Yes
RV Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single Handle with Foam Grip
Wheel Kit Included	Yes
Wheel Size	10 in. Diameter, 2.5 in. Wide
Wheel Type	Polyurethane
Frame Thickness	1.25 in. (32 mm)
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs
Commercial Warranty	6 Months or 1000 hrs
Assembled Length in. (mm)	27.2 in. (690.8 mm)
Assembled Width in. (mm)	26.1 in. (662.94 mm)
Assembled Height in. (mm)	26 in. (660.4 mm)
Extended Length in. (mm)	40.7 in. (1033.9 mm)
Carton Length in. (mm)	31.1 in. (790 mm)
Carton Width in. (mm)	21.4 in. (545 mm)
Carton Height in. (mm)	23.2 in. (590 mm)
Dry Unit Weight lb. (kg)	192 lb. (87 kg)
Shipping Weight lb. (kg)	200 lb. (90.7 kg)
UPC	855464003988
GTIN	00855464003988

09252017KD
©2017 Westinghouse Portable Power
Specifications are subject to change without notice
Westinghouse Portable Power
777 Manor Park Dr., Columbus, OH 43228

**Have questions? Contact our team
at service@wpowereq.com or call
855.944.3571**

