

SPECIFICATIONS

Product Line	STATIC WAVE
Model Number	XS12
Min/Max HP (LOAD)	8 to 12
Voltage	208-240
Hz	50/60
Max 1 Ph. Amps	33.6
Acceptable Load Types	Light to moderate loaded motor loads on Wye wound (2/3 capacity) Delta motors (1/2 capacity)



Company of Manufacture USA

Application Notes

For light to moderate starting or running loads only.

- Intended for wye wound motors. Some delta wound motors may operate but will produce 50% of their nameplate HP.
- Motors will produce 2/3 of rated HP.
- Special loads:
 - May be used for air compressors but should have the motor pulley size reduced by 1/3 in diameter. Alternately, a motor that is 50% larger may be fitted.

Why Choose TEMCo for your Static Phase Converter?

- Proudly Made in the USA - This speaks for it's self.
- Manufacturer since 1968 - That's more than 44 years! We'll be there for you when you need us.
- HD really means HD - Design uses full-voltage rated capacitors and switching controls
- You know quality when you see it - Engineered - Not Just Assembled. Give us a call or drop by & we'll show you how.
- Dedicated Clear Wiring - Input and output terminals simplify and speed wiring.
- Power and Start Cycle indicators - Verify operational status.
- Un-Conditional RETURN POLICY - If you don't love it, We'll take it back and Pay the Shipping!
- Come by and See one for yourself - If you have questions, we want to hear from you. Want to talk shop or pick up your order? Stop by! We'd be glad to have you.