

ESCORT®

Intelligent, Precise
Driver Alert System

iX_c



Don't be confined by the range
of an average radar detector.



Patented AutoLearn
Rejects False Alerts



Live Detection &
Limitless Range with
ESCORT Live app



Connected Car
Compatible


Owner's Manual

Congratulations



ESCORT iXc

You've just purchased the ESCORT iXc with long-range radar-laser performance, GPS-based intelligence plus Bluetooth® and Wi-Fi connectivity.



ESCORT iXc features a new multi-color

OLED display.

Brilliant graphics


illuminate intuitive

icons that identify

the type of threat at a glance.

ESCORT iXc Features

- The ESCORT iXc delivers long-range warning on all radar bands including X, K, Supersweep Ka.
- ESCORT iXc's GPS location-based intelligence automatically locks out false alerts and allows you to mark locations for future reference.
- ESCORT iXc gives you access to ESCORT's DEFENDER Database, which warns you of verified speed traps, speed cameras, and red light cameras.
- ESCORT iXc, with built in Bluetooth® and Wi-Fi technology, gives you access to ESCORT's award winning app, ESCORT Live. Our exclusive real-time ticket-protection, the network which warns you of upcoming alerts received and reported by other users in the area, and gives you access to local speed limit data for over-speed alerts.



Live Ready!

I N T E L L I G E N T L O N G - R A N G E R A D A R - L A S E R D E T E C T O R

Registration, ESCORT Live, Wi-Fi Connect

Before downloading ESCORT Live, you must first register your ESCORT iXc device. Be sure to have your ESCORT iXc unit nearby, as you will need its serial number.

- 1 Visit www.EscortRadar.com and click Product Registration.
- 2 Click the “Registration for all devices” link.
- 3 Follow the onscreen instructions to register your device.

Be sure to write down the username and password you create, as you will need this information to access and download ESCORT Live. (You will also receive an e-mail with this information, once you have registered your device.)

For iPhone:

- 1 Ensure ESCORT iXc power is ON
- 2 Open the App Store on your iPhone and search for **ESCORT Live Radar**.
- 3 Follow the onscreen instructions to download **ESCORT Live Radar** and then open the app.
- 4 When prompted, enter the username and password you created when registering your product at EscortRadar.com.
- 5 Press the Settings button  then select **Devices**.
- 6 You should see **iXc** listed with Not Connected underneath. Press the **iXc** device entry and when prompted select Pair.
- 7 The Bluetooth icon on the ESCORT iXc display will appear to confirm that it is paired to your iPhone.



For Android based smartphones:

- 1 Ensure ESCORT iXc power is ON.
- 2 On your smartphone go to Bluetooth® Settings and make sure that Bluetooth® is ON.
- 3 Open Google Play on your smartphone and search for **Escort Live Radar**.
- 4 Follow the onscreen instructions to download **ESCORT Live Radar** and then open the app.
- 5 When prompted, enter the username and password you created when registering your product at EscortRadar.com.
- 6 In the Escort Live app, press the red Bluetooth® button and select **iXc** from the popup menu.



Using Wi-Fi Connect:

Connecting ESCORT iXc to a Wi-Fi network is as easy as **1, 2, 3:**

- 1 Register your ESCORT iXc. Remember the email and password that you used.
- 2 Install the ESCORT Live app on your smartphone and pair ESCORT iXc to your smartphone's Bluetooth (see previous section for directions). Login to ESCORT Live using the email and password used when you registered your ESCORT iXc.
- 3 Connect your smartphone to the Wi-Fi network and go to ESCORT Live's Wi-Fi Settings menu to enter the network's password.

After successfully connecting to a Wi-Fi network, the speed limit indicator on your ESCORT iXc will change to white indicating that is receiving data from Wi-Fi (see page 6). Software updates, speed limit data, and ESCORT Live alerts are provided when connected to a Wi-Fi network.

Note: ESCORT iXc only supports 2.4 GHz Wi-Fi (802.11 b/g/n).

Installation

Your new detector comes with our latest **EZ Mag Mount™**. Simply tilt the display end of the detector up and slide it onto the mounting bracket. The magnetic mount holds the detector in place. To remove the detector from the mount, simply lift the display end of the detector and the detector releases from the mount.

Mounting Tips:

- Center of windshield between driver and passenger.
- Ensure clear view of road ahead and sky above.
- Avoid windshield wipers and heavily tinted areas.


To mount the detector in your vehicle:

- 1 Remove paper backing from EZ Mag Mount™ StickyCup.
- 2 Ensure the locking clamp is open.

- 3 Firmly press EZ Mag Mount™ StickyCup onto windshield and close the locking clamp to secure.
- 4 To adjust view, loosen thumb wheel and adjust angle of mounting bracket. Tighten thumb wheel to secure.
- 5 Tilt the display end of the detector slightly upward and engage with the flanged edge of the mounting bracket. The EZ Mag Mount™ magnet holds the detector in place.
- 6 To remove the detector, simply lift the display end of the detector upward. The ESCORT iXc will release from the mount.
- 7 To remove mount from windshield, release locking clamp and pull tab on top of StickyCup.

EZ Mag Mount™ Care Instructions:

Should the EZ Mag Mount™ StickyCup accumulate debris and lose its stickiness, simply rinse under warm water, gently wipe off debris and allow to air dry.




Controls & Features

Using ESCORT iXc

- 1 Plug small end of SmartCord USB into modular jack on ESCORT iXc and large end of SmartCord USB into your car's lighter/accessory socket.
- 2 ESCORT iXc should power on automatically. If not, press the device's power button. 

Earphone Jack

Connects to optional 3.5 mm stereo earphone



Mini USB Jack

Connects to your computer via USB A / Mini B cable for downloading software updates

Modular Jack

Connects to SmartCord USB for powering your device

Using SmartCord USB

• Mute Button:

- Press to mute the audio for a specific alert.
- Press three times to lock out a false alert.
- Press twice while receiving a locked-out alert to unlock.
- When connected to ESCORT Live press and hold mute button on unit or cord to manually report to other users a verified X or K-band alert, or a police officer observing traffic.

• **Alert Light:** Blinks red when receiving a radar or laser alert.

• **Power Light:** Lights green when receiving power.

• **USB Charging Port:** Charge smartphones, tablets and other USB-charged Devices.



Modular Connector

Plugs into detector jack

SmartCord USB Adapter

Connects to lighter/accessory socket

Controls & Features



Mount Area
The EZ Mag Mount™ attaches to device here

Power 
Press to turn ESCORT iXc on or off

Volume
Press and hold + or – to adjust volume

Brightness (BRT)
Press to adjust display brightness (Min, Med, Max, Auto, Dark)

Sensitivity (SEN)
Press to adjust detector sensitivity (Auto, Auto NoX, AutoLoK, and Highway)

Mute
Press to mute an alert; press three times to lock out a false alert; press twice while receiving a locked-out alert to unlock

Display
Alert area

Display (OSP)
Current speed

Mark Location (MRK)
To mark a location for future alerts, press MRK twice, then VOL + or – to select the type of marker, then MRK again to confirm. Press twice while receiving marker alert to unmark

Display (OSP)
OverSpeed alert setting, can be adjusted in Preferences. Bluetooth icon will appear here when paired to phone. Speed limit data will appear here when receiving ESCORT Live data from smartphone's bluetooth or from vehicle's Wi-Fi.

70 OSP	45		OverSpeed Alert
	45		Bluetooth
55 MPH	45		Speed Limit Data
55 MPH	45		Speed Limit Data

Data from Bluetooth

Data from Wi-Fi

Settings & Preferences

Press and hold the MRK and SEN buttons to access Preferences. To exit Preferences, simply wait a few seconds without pressing a button. The unit will display **Completed** to confirm your selections.

Press MRK to go from one category to the next

Press VOLUME + or – to change your setting within a category

User Mode	Advanced* Novice	Access and customize all Settings and Preferences Access and customize units and display color, (all other Settings are set to factory defaults) <i>NOTE: Switch back to advanced mode to view all Preferences.</i>
Pilot	Scan Bar* Full Word	Scanning Bar with Full Word. Full Word: Auto, Auto NoX, AutoLoK or Highway
Display Color	Blue*/Green/Red/Amber	Set color to match your vehicle's dash display
Speed Display	On* Off	Displays current speed Displays battery voltage
Cruise Alert	20 mph* Off / 20-160 mph	Offers double beep alert tones below specified speed
Over Speed	70 mph* Off / 20-160 mph	Reminds you when you exceed a specified speed
Over Speed Limit	Speed Limit* Off / Speed Limit/5 Over/7 Over/10 Over/15 Over/20 Over/25 Over	Reminds you when you reach a specified speed at or over the speed limit
Meter Mode	Standard* Spec Expert Simple Caution Slow Down	Single band with signal strength bar graph Single band with numeric frequency Multiple bands with signal strength bar graphs Simple messages replace bands: (if traveling below cruise alert limit) (if traveling above cruise alert limit)
Tones	Standard* Mild	Standard ESCORT alert tones Mild doorbell chime alert tones
AutoMute	AutoMute Low / Med* / High / Off	Automatically reduces audio to preferred volume during alert
AutoLearn	On* / Off	Automatically stores and locks out false alarms
Units	English* / Metric	Units for distance and speed
Language	English* / Espanol	Language for voice and text
Voice	On* / Off	Voice announcements
GPS Filter	On* / Off	Enables GPS-powered features

AutoPower **Off**

1 Hour

2 Hours

4 Hours*

8 Hours

Power turns on or off depending on your vehicle's ignition type (constant power or switched)

Powers off automatically after 1 hour

Powers off automatically after 2 hours

Powers off automatically after 4 hours

Powers off automatically after 8 hours

NOTE: AutoPower only works with constant power ignition.

NOTE: If AutoPower is on, to save screen life the display screen goes blank after 30 minutes without moving. Display screen will turn on automatically after you reach 10MPH.

Band Enables **Default***

Modified

Default Settings

Band Enables have been modified from their default settings

Press SEN to go from one band category to the next

Press VOLUME + or - to change your setting within a category

X Band **On* / Off**

K Band **On* / Off**

Freq: 24.050 – 24.250 GHz

NOTE: When K Band is off, you can select separate segments of the band to turn on or off.

KN1 **On* / Off**

KN2 **On* / Off**

KN3 **On* / Off**

KN4 **On / Off***

Ka Band **On / Off***

Freq: 24.050 - 24.110 GHz

Freq: 24.110 - 24.175 GHz

Freq: 24.175 - 24.250 GHz

Freq: 23.950 - 24.050 GHz

Freq: 33.400 - 36.000 Ghz

NOTE: When Ka Band is off, you can select separate segments of the band to turn on and off.

KaN1 **On / Off***

KaN2 **On* / Off**

KaN3 **On / Off***

KaN4 **On / Off***

KaN5 **On* / Off**

Freq: 33.400 - 33.700 GHz

Freq: 33.700 - 33.900 GHz

Freq: 33.900 - 34.200 GHz

Freq: 34.200 - 34.600 GHz

Freq: 34.600 - 34.800 GHz

KaN6 **On / Off*** Freq: 34.800 - 35.160 GHz

KaN7 **On / Off*** Freq: 35.160 - 35.400 GHz

KaN8 **On* / Off** Freq: 35.400 - 35.600 GHz

KaN9 **On / Off*** Freq: 35.600 - 35.840 GHz

KaN10 **On / Off*** Freq: 35.840 - 36.000 GHz

Ka-POP **On / Off***

Laser **On* / Off**

TSR **On* / Off**

RDR **On / Off***

Automatically rejects traffic flow sensors-monitoring false alarms

Radar Detector Rejection

Marker Enables **Default***

Modified

Default Settings

Marker Enables have been modified from their default settings

Wi-Fi **On* / Off**

Bluetooth **On* / Off**

Auto Update **Off/Defender/Software/All***

Perform Update **Defender Software**

Turns Wi-Fi Connect on or off

Turns Bluetooth on or off

Automatically checks for selected updates when detector is powered on

Defender update. Press SEN to confirm

Perform Software update. Press SEN to confirm

Press SEN to go from one marker category to the next

Other
Redlight
Red & Speed
Speed Cam
Speed Trp
Air Patrol

Clear Locations

On* / Off
On* / Off
On* / Off
On* / Off
On* / Off
On / Off*

Marked
Lockouts
Defender
Format

Press VOLUME + or – to change your setting within a category

Other location
Red light camera
Red light & speed camera
Speed camera
Speed trap
Known aircraft patrolled areas

NOTE: User cannot mark an air patrol location.

Clear all user Marked locations. Press SEN button to confirm
Clear all lockouts. Press SEN button to confirm
Clear all DEFENDER data. Press SEN button to confirm
Clear DEFENDER database, all markers, and all lockouts
Press SEN button to confirm

*Default Setting

Notes for Settings & Preferences

To view serial number and software revision press MRK and MUTE while powering on detector.

To restore ESCORT iXc to its original factory Settings, press and hold SEN and BRT while turning the power on.

A "Restored" message will display, acknowledging the reset.

Software Updates

In its factory default settings ESCORT iXc automatically receives software updates from your connected vehicle's Wi-Fi network. See Using Wi-Fi Connect on page 5 for connection instructions.

The ESCORT iXc operating firmware and red light and speed camera database can also be updated using a USB A/Mini B cable (not included) connected to a computer using our detector software tools found on our web site. In order to have access to these updates, please register your ESCORT iXc at www.EscortRadar.com

Warranty

ESCORT One Year Limited Warranty

What this warranty covers: Escort, Inc. ("Escort") warrants your Product against all defects in materials and workmanship.

For how long: One (1) year from the date of original purchase from an authorized Escort dealer.

What we will do: If a breach of warranty occurs, Escort, at its discretion, will either repair or replace your Product free of charge.

What we will not do: Escort will not pay shipping charges that you incur for sending your Product to us.

What you must do to maintain this warranty: Show original proof of purchase or receipt from an authorized Escort dealer.

Warranty exclusions: This warranty does not apply to your product under any of the following conditions: 1. The serial number has been removed or modified. 2. Your product has been subjected to misuse or damage (including water damage, physical abuse, and/or improper installation). 3. Your product has been modified in any way. 4. Your receipt or proof-of-purchase is from a nonauthorized dealer or internet auction site, including E-bay, U-bid, or other non-authorized resellers. 5. You are not the original purchaser of the Product from an authorized dealer or did not receive it as a gift from the original purchaser of the Product from an authorized dealer.

To obtain service: 1. Contact ESCORT (1-800-543-1608) to obtain a Return Authorization Number. 2. Properly pack your Product and include: your name, complete return address, written description of the problem with your Product, daytime telephone number, and a copy of the original proof of purchase or receipt. 3. Label the outside of the package clearly with your Return Authorization Number. Ship the Product pre-paid (insured, for your protection) to: ESCORT, Inc., 5440 West Chester Rd., West Chester, OH 45069.

LIMITATION OF WARRANTY: The obligations set forth above are ESCORT's sole obligations and your exclusive remedy. **ESCORT makes no other express warranty. Any implied warranty of merchantability or fitness for a particular purpose that may be applicable to the Product is limited in duration to the duration of this warranty.** Some States do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. **ESCORT SHALL NOT BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INCIDENTAL DAMAGES INCLUDING, WITHOUT LIMITATION, DAMAGES ARISING OUT OF THE USE, MISUSE OR MOUNTING OF THE PRODUCT.**

Some States do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. ESCORT is not responsible for products lost in shipment between the owner and our service center.

Other legal rights: This warranty gives you specific legal rights, and you may also have other rights which vary from State to State.

©2018 ESCORT Inc. ESCORT® is a registered trademark of ESCORT Inc.

Contact Us

Accessories



800.433.3487



EscortRadar.com

Designed in the USA by Escort, Inc.
Manufactured in the Philippines

ESCORT Inc.
5440 West Chester Road
West Chester OH 45069

Sales / Service 800.433.3487
www.EscortRadar.com

©2018 ESCORT Inc. ESCORT®, ESCORT iXc®, Defender®, AutoLearn®, TrueLock™, AutoSensitivity™, SpecDisplay™, ExpertMeter™, ESCORT Live™, IVT Filter™, SmartMute™ and EZ Mag Mount™ are trademarks of ESCORT, Inc.

FCC NOTE: Modifications not expressly approved by the manufacturer could void the user's FCC granted authority to operate the equipment.

FCC ID: QKLXC. CONTAINS FCC ID: TFB-1003

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received including interference that may cause undesired operation.

ESCORT Live Compatible



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by ESCORT is under license.